



A-A SECTION



| 8   | Contact Terminals    | Brass    | Silver Ptd. | 6    |
|-----|----------------------|----------|-------------|------|
| 7   | 6P Housing           | PA66     |             | 1    |
| 6   | Spring Ring          | Steel    | Nickel Ptd. | 1    |
| 5   | Setscrew             | Steel    | Nickel Ptd. | 1    |
| 4   | T Holder             | Steel    | Nickel Ptd. | 1    |
| 3   | Strain Boot          | PVC      |             | 1    |
| 2   | YE-122XB Screw Cap   | Brass    | Nickel Ptd. | 1    |
| 1   | YE-122XB Shell Cover | Brass    | Nickel Ptd. | 1    |
| No. | Description          | Material | Treat       | Q'ty |

**Specifications**  
 rating :

100V AC 1A MAX

 contact resistance :  
 pins-30mΩ MAX; shell-50mΩ MAX

 insulation resistance :  
 MIN 100 MEGΩ @500V DC

 voltage withstand :  
 250V AC R.M.S. for 1 minute

APPROVED BY :



Date: JUN 21 200

Description:

6P DIN CABLE PLUG SCREW LOCKING

Part No.:

YE-1226B

YE-1226B

**ULTIMAX** <sup>®</sup>  
 THE ULTIMATE ELECTRONIC COMPONENTS